



Solid Products, Inc.
3290 Industrial Rd.
Richfield, WI 53076

Phone: 1-(262) 628-3840
Fax: 1-(262) 628-4068

Description

FAST 5 Drywall Surfacers is a high-build interior coating that is used in lieu of a skim coat of joint compound to provide a LEVEL 5 GYPSUM BOARD FINISH as described in ASTM C 840 and Gypsum Association Specification GA-214. **FAST 5** Drywall Surfacers is applied with an airless sprayer eliminating the time consuming labor of skimming the entire drywall surface with joint compound.

Advantages

- Faster than skim coating with joint compound.
- Save labor over other methods.
- Provides a surface that is more resistant to damage than joint compound and wallboard paper.
- May be used as a block filler.

- Is sandable if a smoother surface is required.

Limitations

- Can only be applied with an airless sprayer capable of spraying a minimum of 1 gallon per minute or more.
- Not able to be rolled or backrolled.
- Poor spray techniques can cause an orange peel texture.

Composition

Materials CSA No.
 Calcium carbonate 1317-65-3
 Water 7732-18-5
 Acrylic Resins
 (Proprietary)
 Titanium dioxide 13463-67-7
 Clay 1332-58-7
 Clay 12174-11-7
 Ethylene glycol
 107-21-1

Packaging

5 gallon pail (18.9 liters)

Technical Data

Color – White
Flash point – Non-flammable
Coverage – Approximately 100 square feet per gallon.
Cleanup – Use warm soapy water to clean equipment.

Job Name _____

Contractor _____

Date _____

**Submittal Approvals:
(Stamps or Signatures)**